


Milled Fiber MF 7904



Polymer

PTFE and others

LANXESS Glass Fiber MF 7904* is suitable for a wide range of applications where the reinforcing properties of glass fiber are needed in combination with very small initial fiber length, no surface treatment and excellent flowability. It can be used, for example, for the reinforcement of polytetrafluoroethylene.

Product Description

Very small initial average fiber length of 50 µm (nominal)

No surface treatment / sizing

Technical Characteristics

Fiber Diameter (nom.)	14 µm
Av. Fiber Length (nom.)	50 µm
Glass	E-Glass (DIN 1259)
Size	-
Moisture content	≤ 0,05 wt%
Bulk density	approx. 920 kg / m³
(Original data ex works)	

Packaging

Cardboard box, Octabin (see detailed information on next page)

Storage

The glass fiber should be stored in a dry place, preferably at room temperature and 50 - 70 % relative humidity.

Contact

For further information please contact:

Mail glassfiber@lanxess.com
Phone +49 (0)221 8885 7275

Packaging Information

MF 7904

Cardboard box with plastic bag

Net Weight Box	25 kg
Net Weight Pallet	1000 kg (40 boxes)
Dimensions Box	390 x 290 x 275 mm
Dimensions Pallet	1000x1200x138 mm (CP1)
Packaging Code	ZX 00 – RA100D



Octabin

Net Weight	750 kg
Dimensions Octabin	1086 x 1086 x 870 mm
Dimensions Pallet	1140x1140x138 mm (CP3)
Packaging Code	ZK 75



Disclaimer

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

Values

Unless specified to the contrary, the values given have been established on standardized test. The figures should be regarded as guide values only and not as binding minimum values.

